



HE4621

Product Data Sheet

HE4621 is a difunctional aromatic polyurethane acrylate oligomer.

Characteristics

HE4621 is a difunctional aromatic polyurethane acrylate oligomer. This product has the characteristics of fast curing speed, good surface scratch resistance and good toughness. It is suitable for paper varnish, silk screen and flexographic printing, wooden floor, plastic and PVC coatings. When used with epoxy acrylate resin, it can significantly improve the toughness and surface scratch resistance of epoxy acrylate.

Delivery form

100% active ingredients;

Product parameters

Functional base (theoretical): 2

Viscosity (25°C, NDJ rotational viscometer): 15000-30000 mPa.s

Color number (APHA): ≤ 200

Appearance: colorless or yellowish clear liquid

Principal properties

Low viscosity;

Good toughness;

Fast curing speed;

Good surface scratch resistance.

Applications

Suitable for paper varnish, silk screen and flexographic printing, wooden floor, plastic and PVC coatings and other fields.

Storage guidelines

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature no more than 30°C. Exposure to direct sunlight should be avoided.

Shelf life

Under above mentioned storage condition, the shelf life of the resin will be 120 days after production.

For more than 120 days, the goods are still owned by ZOHO Company, the company's QC can make the corresponding extension of the shelf life after testing qualified.

Material safety

This product data sheet only applies to the latest version of Material Safety Data Sheet. Any updates to safety-related information that are consistent with legal requirements will only be reflected in the safety data sheet, at the same time the Sheet will be updated and published. Information on current classification and labelling, application and process methods, and more safety-related data can be found in the latest Material Safety Data Sheet.