



HE8760 is a solvent-based, soybean oleic acid-based long oily alkyd resin.

#### Characteristics

It is used to prepare self-drying anticorrosive paint and alkyd magnetic paint for containers, ships and construction machinery.

# delivery form

70% in xylene/S-150#;

# **Product specifications**

Solid Content: 68.0–72.0%

Viscosity (25°C, NDJ rotational viscometer): 2.0-3.0 Pa.s

Color number  $\leq 5 \# \text{ (Fe-Co)}$ 

Acid value 4.0-10.0 mgKOH/g

Appearance clear and transparent

The following items are not required:

flash point 25°C

density (20°C) 0.99-1.03 g/ml

# Principal properties

High gloss;

Long oiliness, quick drying;

strong adhesion;

Excellent adhesion to metals.

### **Applications**

It is used to prepare self-drying anticorrosive paint and alkyd magnetic paint for containers, ships and construction machinery.

# Compatibility with resins and solvents

HE1762	-	HE1767	-	xylene	+	2- Butoxyethanol	+
HE8780	1	CAB- 381-20	1	trimethy lbenzen e	+	CAC	+
1/2NC	+			butyl acetate	+	n-butanol	+
				Cyclohe xanone	+		

big red paste	e	big red paint		
HE8760	55	HE8760	50	
pigment Scarlet Powder	24	HE8760 big red paste	30	
BYK110	3	complex drier	2.5	
xylene	18	1% silicone fluid	0.4	
		anti-crusting agent	0.2	
		xylene	10	
		toluene	6.9	

#### Storage guidelines

Reference recipe

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature no more than 30°C. Exposure to direct sunlight should be avoided.

#### Shelf life

Under above mentioned storage condition, the shelf life of the resin will be 12 months after production.

For more than 12 months, the goods are still owned by ZOHO Company, the company's QC can make the corresponding extension of the shelf life after testing qualified.

#### Material safety

This product data sheet only applies to the latest version of Material Safety Data Sheet. Any updates to safety-related information that are consistent with legal requirements will only be reflected in the safety data sheet, at the same time the Sheet will be updated and published. Information on current classification and labelling, application and process methods, and more safety-related data can be found in the latest Material Safety Data Sheet.

Note: + means soluble/miscible; Omeans partially soluble/partially miscible;

means insoluble/incompatible.